(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 12 February 2004 (12.02.2004)

PCT

(10) International Publication Number WO 2004/013955 A1

(51) International Patent Classification7:

H03D 3/00

(21) International Application Number:

PCT/IB2003/003191

11 July 2003 (11.07.2003) (22) International Filing Date:

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 02/09744

31 July 2002 (31.07.2002) FR

- (71) Applicant (for all designated States except US): KONIN-KLLIKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HUMBERSOT, Alexandre [FR/FR]; 156 Boulevard Haussmann, F-75008 Paris (FR).
- OUDHEUSDEN-PERSET, Laure; Société 74) Agent: Civile SPID, 156 Boulevard Haussmann, F-75008 Paris


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: RECEIVER COMPRISING MULTIPLE PARALLEL RECEPTION MEANS



(57) Abstract: The invention relates to a receiver for receiving an analog signal having a spectrum situated in a given frequency band higher than the baseband. It comprises reception means which manage at least one narrow-band noise signal located around a given noise frequency. The receiver comprises a plurality of parallel baseband conversion means defining a plurality of reception channels for converting the spectrum of the received signal in reception bands close to the baseband and shifted with respect to one another so that, on each reception band, the narrow-band noise is superimposed on the shifted spectrum of the received signal at distinct points relative to said spectrum. It also comprises recombination means for recombining the many shifted spectra of the received signal obtained on each reception channel and for obtaining a single spectrum corresponding to the spectrum of the received signal with the effect of the narrow-band noise removed and situated in a frequency band close to the baseband.